



NO  
IMAGE  
AVAILABLE

## FAG Axial-Rillenkugellager - FT5

Bearing No. FT5

|                              |  |
|------------------------------|--|
| d                            | 0.3125 in  |
| axial static load capacity:  | 1100 lbf   |
| misalignment angle:          | 7 °  |
| operating temperature range: | Max 250 ° F  |
| shank thread length:         | 0.8750 in  |
| head diameter:               | 0.9000 in  |
| rod end type:                | Female Threaded  |
| head width:                  | 0.3270 in  |
| shank thread size:           | 5/16-24  |
| ball width:                  | 0.4370 in  |
| thread direction:            | Right Hand   |
| length to ball center:       | 1.6250 in  |
| grade:                       | Military   |
| overall height:              | 2.0750 in  |
| thread type:                 | UNJF-3B  |
| standards met:               | SAE-AS81935, SAE-AMS-QQ-P-416 Type 1 Class 2, SAE-AMS-H-6875, SAE-AMS-H-7199, ASTM-E-1444, SAE-AS81820 SAE-AS81935 SAE-AMS-QQ-P-416 Type 1 Class 2 SAE-AMS-H-6875 SAE-AMS-H-7199 ASTM- |
| lubrication type:            | Self-Lubricating   |
| series:                      | Heim®  |
| housing material:            | 4340 Alloy Steel   |
| manufacturer product page:   | <a href="#">Click here</a>   |

FT5 Bearing 2D drawings and 3D CAD models



|                              |                               |
|------------------------------|-------------------------------|
| ball material:               | 440 C Stainless Steel         |
| Weight                       | 0.10 lbs                      |
| race material:               | 17-4 PH Heat Treated,<br>PTFE |
| manufacturer upc number:     | 637400183196                  |
| radial static load capacity: | 7180 lbf                      |